



FB 300B

Battery powered
reversible vibratory plate

Available during Spring 2021

Emission free compaction of sand, gravel and rock fill.

All our machine models are versatile and easy to operate. They are also durable and reliable, which means lower operating and maintenance costs.

- The FB 300B is a unique product - a battery powered reversible plate for heavy duty use, built on a Swebpac's patented technology.
- The Swebpac FB 300B is ideal for work in areas where combustion engines should not be used, such as trenches, tunnels, urban areas or indoor construction.
- Operating time exceeds 2 hours thanks to the powerful 6.6 kWh Lithium-Ion battery
- RFID key with dead-man-handle function
- Bluetooth connection for reading of runtime and machine status via Swebpac's Service-App.
- The fully covered machine with a robust frame protects the battery and motor from damage.
- Superior ergonomics with an efficiently vibrated handle (HAV <2.5 m/ s²) with forward/backward function and speed control.

Options

- Programable/individualised RFID-key.
- Handle heating.

Swebpac is Sweden's leading manufacturer of soil compactors. The company has a wide range of products, with different motor options and a variety of sizes for every application. Swebpac is certified for quality and environmental management under ISO 9001 and 14001, and our machines are Eurotest-certified by SMP Swedish Machinery Testing Institute. You will find detailed information about the company and our products on our website, www.swebpac.com. We reserve the right to make changes in technical specifications without prior notice.

Swebpac AB
Blockvägen 3 | SE-341 32 Ljungby | Sweden
Tel +46 (0)372-156 00 | www.swebpac.com

TECHNICAL DATA SWE PAC FB 300B

Weight, net	290 kg
Base plate, width	500 mm
Height, max / min	1200 / 1030 mm
Length, max / min	1530 / 900 mm
Motor	Asynchronous motor
Motor output	2.8 kW
Type of battery	Lithium-Ion
Voltage	48 V
Energy content	6.6 kWh
Centrifugal force	38 kN
Frequency	78 Hz
Working speed	0-25 m/min
Hand/arm vibrations HAV according to ISO 5349 on gravel surface	< 2.5 m/s ²
Guaranteed sound-power level, LWA	104 dB(A)
Sound pressure level (at operator's ear), OP	90 dB(A)

Part number

306200 FB 300B incl battery and charger