

PVC CONVERTER



PVC 1.6



PVC 4.5/6.0

Rotative frequency converter.

The PVC high-frequency converters are very robust and durable.

- A strong and reliable traditional-type rotary mechanical frequency converter with an efficient cooling fan. The unit is protected by a robust steel cage, which provides good protection against mechanical damage.

- PVC 4.5 and PVC 6.0 are equipped with transport wheels and handle for easy movement.
- Suited for PVE and PVE-D.

TECHNICAL DATA – SWEPAC PVC

PVC 1.6 230V

Power	1.6 kVA
Primary voltage	230V, 1-phase, 50 Hz
Secondary voltage	42V, 200 Hz
Output current	23 A
Outlet sockets	2
Weight	30 kg

PVC 1.6 400V

Power	1.6 kVA
Primary voltage	400V, 3-phase, 50 Hz
Secondary voltage	42V, 200 Hz
Output current	23 A
Outlet sockets	2
Weight	28 kg

TECHNICAL DATA – SWEPAC PVC

PVC 4.5 400V

Power	4.5 kVA
Primary voltage	400V, 3-phase, 50 Hz
Secondary voltage	42V, 200 Hz
Output current	61 A
Outlet sockets	4
Weight	74 kg

PVC 6.0 400V

Power	6.0 kVA
Primary voltage	400V, 3-phase, 50 Hz
Secondary voltage	42V, 200 Hz
Output current	82 A
Outlet sockets	4
Weight	83 kg

SWEPAC is Sweden's leading manufacturer of soil compactors. The company has a wide range of products, with different motor options and a variety of sizes for every application. SWEPAC is certified for quality and environmental management under ISO 9001 and 14001, and our machines are Eurotest-certified by SMP Swedish Machinery Testing Institute. You will find detailed information about the company and our products on our website, wwwSWEPAC.com. We reserve the right to make changes in technical specifications without prior notice.